

TECHNICAL REPORT FOR EU TYPE-EXAM CERTIFICATION of Personal Protective Equipment (PPE)

EU TYPE EXAMINATION Nº:

UE-000147/00

APPLICATION DATE:

18/01/2022

DATE OF ISSUE:

23/12/2022

APPLICANT:

WELDAS EUROPE B.V
BLANKENWEG 18, 4612 RC BERGEN OP ZOOM
NETHERLAND

PPE TYPE:

SLEEVES

REFERENCE (PPE):

38-4321

INDEX:

1. PPE identification
2. Certification scope
3. Documentation submitted
4. Relationship between this European Standard and Annex II of Regulation (EU) 2016/425 on PPE
5. Design evaluation
6. Comfort evaluation
7. Sizing evaluation
8. Summary of results
9. Conclusion

ANNEX. - EU Type-Examination Certificate

1. PPE IDENTIFICATION

1.1 Description and photograph

Sleeves manufactured in grey fabric. It presents a white elastic at the cuff and top edge as well as a black hook and loop on the outer side.



1.2 Description of the components

PPE components according to the information supplied by the manufacturer:


- Cotton flame retardant fabric with 520 g/m² is used with three ply KEVLAR®
- White elastic band and hook and loop fastening materials for the closures and reinforcements.

1.3 Sizes

The size chart supplied by the manufacturer:

The garment is manufactured in size XL only.

	M	L	XL	2XL	3XL
	48	52	56	60	64
A	170-176	176-180	180-184	184-188	188-196
B	96-104	104-112	112-120	120-128	128-136
C	84-92	92-102	100-112	112-124	124-136
D			52		



Sizing according to: EN ISO 13688 (in CM) id replaces the previous one

1.4 Samples given for certification

On date 14/01/2022, three (3) sleeves size XL arrived in the laboratory.

2. CERTIFICATION SCOPE

- **EN ISO 13688:2013** and **EN ISO 13688:2013/A1:2021** Protective clothing – General requirements.
- **EN ISO 11611:2015** Protective clothing for use in welding and allied processes

For the protection of the arms of the user (except hands) against the following risks:

- Risk of burning due to contact with small splashes of molten metal.
 - Risk of burning due to a short exposure to limited flame.
 - Risk of burning due to radiant heat.
 - Risk of short electric discharge.
- **EN 1149-5:2018** Protective clothing – Electrostatic properties – Part 5: Material performance and design requirements.

For the protection of the arms of the user (except hands) against the following risk:

- Risk of burning due to incendiary discharges.

3. DOCUMENTATION SUBMITTED

Technical documentation, including the next points:

- Complete description of the PPE and of its intended use
- Assessment of the risks against which the PPE is intended to protect
- List of the essential health and safety requirements that are applicable
- Design and manufacturing drawings and schemes of the PPE and of its components and explanations
- Reference of the harmonized standards and/ or other technical specifications
- Reports on the tests carried out to verify the conformity of the PPE
- A description of the means used by the manufacturer during the production (Modulo C)
 - Manufacturer's instructions
 - Marking
 - Declaration of conformity

4. RELATIONSHIP BETWEEN THIS EUROPEAN STANDARD AND ANNEX II OF REGULATION (EU) 2016/425 ON PPE

- EN ISO 13688:2013 and EN ISO 13688:2013/A1:2021 Protective clothing – General requirements.

Essential Health and Safety Requirements, according to Annex II of Regulation (UE) 2016/425	Clause(s) / sub-clause(s) of the standard EN ISO 13688:2013/A1:2021	Result
1.2.1 Absence of risk and other inherent nuisance factors	5.3	Meet <input checked="" type="checkbox"/>
		Not meet <input type="checkbox"/>
		Not applicable <input type="checkbox"/>
1.2.1.1 Suitable constituent materials	4.2	Meet <input checked="" type="checkbox"/>
		Not meet <input type="checkbox"/>
		Not applicable <input type="checkbox"/>
1.2.1.2 Satisfactory Surface condition of all PPE parts in contact with the user	4.4	Meet <input checked="" type="checkbox"/>
		Not meet <input type="checkbox"/>
		Not applicable <input type="checkbox"/>
1.4 Manufacturer's instructions and information	8	Meet <input checked="" type="checkbox"/>
		Not meet <input type="checkbox"/>
		Not applicable <input type="checkbox"/>
2.12 PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	6; 7	Meet <input checked="" type="checkbox"/>
		Not meet <input type="checkbox"/>
		Not applicable <input type="checkbox"/>

- EN ISO 11611:2015 Protective clothing for use in welding and allied processes

Essential requirements of Annex II of the EU Directive 89/686/EEC ⁽¹⁾	Clause(s) / sub-clause(s) of the standard EN ISO 11611:2015	Result
1.2.1. Absence of inherent risk and other nuisance factors	4.1; 4.2; 4.3; 4.5; 4.6; 4.7; 6.6; 6.10 y 6.11	Meet <input checked="" type="checkbox"/>
		Not meet <input type="checkbox"/>
		Not applicable <input type="checkbox"/>
1.3.1 Adaptation of PPE to user morphology	4.4	Meet <input checked="" type="checkbox"/>
		Not meet <input type="checkbox"/>
		Not applicable <input type="checkbox"/>
1.4 Manufacturer's instructions and information	5.2; 8	Meet <input checked="" type="checkbox"/>
		Not meet <input type="checkbox"/>
		Not applicable <input type="checkbox"/>
2.4 PPE subject to ageing	5.3	Meet <input checked="" type="checkbox"/>
		Not meet <input type="checkbox"/>
		Not applicable <input type="checkbox"/>
1.3.2 Lightness and strength	6.2; 6.3; 6.4 y 6.5	Meet <input checked="" type="checkbox"/>
		Not meet <input type="checkbox"/>
		Not applicable <input type="checkbox"/>
3.6.1 PPE constituent materials and other components	6.7; 6.8; 6.9	Meet <input checked="" type="checkbox"/>
		Not meet <input type="checkbox"/>
		Not applicable <input type="checkbox"/>
3.6.2 Complete PPE ready for use	6.8; 6.9	Meet <input checked="" type="checkbox"/>
		Not meet <input type="checkbox"/>
		Not applicable <input type="checkbox"/>
1.1.2.2 Classes of protection appropriate to different levels of risk	6.1; 6.8 y 6.9	Meet <input checked="" type="checkbox"/>
		Not meet <input type="checkbox"/>
		Not applicable <input type="checkbox"/>

Rev.1 This version cancels and replaces the previous one

Essential requirements of Annex II of the EU Directive 89/686/EEC ⁽¹⁾	Clause(s) / sub-clause(s) of the standard EN ISO 11611:2015	Result
2.12 PPE bearing one or more identification markings or indicators direct	7	Meet <input checked="" type="checkbox"/>
		Not meet <input type="checkbox"/>
		Not applicable <input type="checkbox"/>

⁽¹⁾ Warning: In order to comply with this non-harmonized standard according to Regulation (EU) 2016/425, the risk assessment carried out by the manufacturer, in its technical documentation, shall be studied and thus assess whether or not it is necessary to add any requirement granting compliance with the applicable minimum essential health and safety requirements, for the type of risk to which the user may be exposed.

- **EN 1149-5:2018** Protective clothing – Electrostatic properties – Part 5: Material performance and design requirements

Essential Health and Safety Requirements, according to Annex II of Regulation (EU) 2016/425	Clause(s) / sub-clause(s) of the standard EN 1149-5:2018	Result
1.4 Manufacturer's instructions and information	4.1 y 6	Meet <input checked="" type="checkbox"/>
		Not meet <input type="checkbox"/>
		Not applicable <input type="checkbox"/>
2.6 PPE for use in potentially explosive atmospheres	4.2	Meet <input checked="" type="checkbox"/>
		Not meet <input type="checkbox"/>
		Not applicable <input type="checkbox"/>
2.12 PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	5	Meet <input checked="" type="checkbox"/>
		Not meet <input type="checkbox"/>
		Not applicable <input type="checkbox"/>

5. DESIGN EVALUATION

- **EN ISO 11611:2015** Protective clothing for use in welding and allied processes

Requirement
After design evaluation according to point 4 of EN ISO 11611:2015, the PPE is determined to be:
Conforming <input checked="" type="checkbox"/> Non-conforming <input type="checkbox"/>

- **EN 1149-5:2018** Protective clothing – Electrostatic properties – Part 5: Material performance and design requirements

Requirement
After design evaluation according to point 4.2.2 of Standard EN 1149-5:2018, the PPE is determined to be:
Conforming <input checked="" type="checkbox"/> Non-conforming <input type="checkbox"/>

6. COMFORT EVALUATION

- **EN ISO 13688:2013 and EN ISO 13688:2013/A1:2021** Protective clothing – General requirements.

Requirement
After the comfort evaluation according to point 4.4 of Standards EN ISO 13688:2013 and EN ISO 13688:2013/A1:2021, the PPE is determined to be:
Conforming <input checked="" type="checkbox"/>
Non-conforming <input type="checkbox"/>

7. SIZING EVALUATION

- **EN ISO 13688:2013 and EN ISO 13688:2013/A1:2021** Protective clothing – General requirements.

Requirement
After evaluation of the sizing according to point 6 and Annex D of Standard EN ISO 13688:2013 and EN ISO 13688:2013/A1:2021, it is determined that the PPE is:
Conforming <input checked="" type="checkbox"/>
Non-conforming <input type="checkbox"/>

8. SUMMARY OF RESULTS

LEGEND RESULTS	
M	Meet
NM	Not meet
NA	Not applicable
NT	Not tested

- EN ISO 13688:2013 and EN ISO 13688:2013/A1:2021 Protective clothing – General requirements.

TEST	APPLIES ON	STANDARD	REQUIREMENTS	*UoM.	REPORT Nº	RESULT
Cr (VI) Innocuousness point 4.2	Each layer of material (Leather)	ISO 17075-1:2017 or ISO 17075-2:2017	EN ISO 13688:2013/A1:2021, point 4.2, a) Shall not exceed < 3mg/kg	NA	NA	NA
Nickel Innocuousness point 4.2	All metallic materials which could come in contact with the skin	EN 1811:2011+A1:2015	EN ISO 13688:2013/A1:2021, point 4.2, b) Shall have a release of nickel of less than < 0,5µg/cm ² per week.	NA	NA	NA
pH Innocuousness point 4.2	Grey fabric / Hook and loop / White elastic band	Textile ISO 3071:2020 Leather ISO 4045:2018	EN ISO 13688:2013/A1:2021, point 4.2 c) Greater than 3,5 and less than 9,5	± 0,3	AR-22-YL- 004012-01	M
Azo colorants which release carcinogenic amines listed Innocuousness point 4.2	Grey fabric / Hook and loop	ISO 14362-1:2017 and ISO 14362- 3:2017 ⁽¹⁾	EN ISO 13688:2013/A1:2021, point 4.2 Shall be no detectable	NA	AR-22-YL- 004012-01	M
Comfort point 4.4	Protective clothing	EN ISO 13688:2013, point 4.4 and EN 13921	EN ISO 13688:2013, point 4.4 and Annex C	NA	Point 6 of this report	M
Dimensional change due to cleaning after pre- treatment point 5.3	Protective clothing o textile	Washed ISO 5077 Dry cleaned ISO 3175-1	EN ISO 13688:2013 + EN ISO 13688:2013/A1:2021, point 5.3 ≤ ±3% (woven) or ≤ ±5% (Knitted)	L & C: ± 0,1 %	AR-22-YL- 004012-01	M
General size designation point 6	Protective clothing	ISO 8559-1:2017, EN ISO 13688:2013 + EN ISO 13688:2013/A1:202 1, point 6 and Annex D	EN ISO 13688:2013 + EN ISO 13688:2013/A1:2021, point 6 and Table 1	± 1 mm	Point 7 of this report	M
Marking point 7	EN ISO 13688:2013 + EN ISO 13688:2013/A1:2021, point 7 and Annex E			NA	NA	M
Information supplied by the manufacturer point 8	EN ISO 13688:2013 + EN ISO 13688:2013/A1:2021, point 8			NA	NA	M

(1) The Azo colorants are tested according to ISO 17234-2:2011 and ISO 17234-1:2020 when leather material.

- EN ISO 11611:2015 Protective clothing for use in welding and allied processes

TEST	APPLIES ON	STANDARD	REQUIREMENTS	*UoM.	REPORT N°	RESULT
General and design requirements point 4	-	EN ISO 11611:2015, point 4 and EN ISO 13688	EN ISO 11611:2015, point 4	NA	Point 5 of this report	M
Pre-treatment ⁽¹⁾ point 5.2	Materials / garment <i>5 washing cycles at 60°C, line dry (Type A)</i>	-	EN ISO 11611:2015, point 5.2	NA	AR-22-YL- 004012-01	M
Ageing ⁽¹⁾ point 5.3	Materials / garment	-	EN ISO 11611:2015, point 5.3	NA	NA	NA
Classification point 6.1	Garment	EN ISO 11611:2015	EN ISO 11611:2015, point 6.1, Annex A Class 1 / Class 2	NA	NA	Class 2
Tensile strength, after pre- treatment point 6.2	Grey fabric	ISO 13934-1 (woven) ISO 3376 (leather)	EN ISO 11611:2015, point 6.2 ≥ 400N (woven) ≥ 80N (leather)	± 13 N	AR-22-YL- 004012-01	M
Tear strength, after pre- treatment point 6.3	Grey fabric	ISO 13937-2 (woven) ISO 3377-1 (leather)	EN ISO 11611:2015, point 6.3 Class 1 ≥ 15N Class 2 ≥ 20N	± 1 N	AR-22-YL- 004012-01	Class 2 M
Burst strength, after pre- treatment point 6.4	Knitted outer materials	ISO 13938-1 or ISO 13938-2	EN ISO 11611:2015, point 6.4 ≥ 100 kPa (50cm ²) ≥ 200 kPa (7,3cm ²)	NA	NA	NA
	Structural seams in knitted materials			NA	NA	NA
Seam strength, after pre- treatment point 6.5	Open grey fabric- grey fabric seam	ISO 13935-2	EN ISO 11611:2015, point 6.5 ≥ 225 N	± 20 N	AR-22-YL- 004012-01	M
Dimensional change, after pre-treatment point 6.6	Garment or each fabric layer	ISO 5077, point 6.6	EN ISO 11611:2015, point 6.6 ≤ ±3% (woven) ≤ ±5% (knitted)	± 0,1 %	AR-22-YL- 004012-01	M
Limited flame spread of the new material (Procedure A) Outer face point 6.7.2	Grey fabric	EN ISO 11611:2015, point 6.7.2, 6.7.3 and ISO 15025	EN ISO 11611:2015, point 6.7.2 The flame does not reach the upper or either vertical edge No flaming or molten debris - No hole formation - Afterglow ≤ 2s - Afterflame ≤ 2s	± 8,8 %	AR-22-YL- 004012-01	M
Limited flame spread, after pre-treatment (Procedure A) Outer face point 6.7.2	Grey fabric			± 8,8 %	AR-22-YL- 004012-01	M
Limited flame spread of the new material (Procedure B) ⁽¹⁾ point 6.7.3	Grey fabric			EN ISO 11611:2015, point 6.7.3 The flame does not reach the upper or either vertical edge No flaming or molten debris - Afterglow ≤ 2s	± 8,8 %	AR-22-YL- 004012-01

Rev.1 This version cancels and replaces the previous one

TEST	APPLIES ON	STANDARD	REQUIREMENTS	*UoM.	REPORT Nº	RESULT
Limited flame spread, after pre-treatment (Procedure B) ⁽¹⁾ point 6.7.3	Grey fabric		- Afterflame ≤ 2s	± 8,8 %	AR-22-YL-004012-01	M
Limited flame spread, after pre-treatment (Procedure A) point 6.7.2	Open grey fabric-grey fabric seam		EN ISO 11611:2015, point 6.7.3 The flame does not reach the upper or either vertical edge No flaming or molten debris	± 8,8 %	AR-22-YL-004012-01	M
Limited flame spread, after pre-treatment (Procedure B) ⁽¹⁾ point 6.7.3	Open grey fabric-grey fabric seam		No flaming or molten debris - Afterglow ≤ 2s - Afterflame ≤ 2s Seams do not separate	± 8,8 %	AR-22-YL-004012-01	M
Limited flame spread, after pre-treatment (Procedure A) point 6.7.2	Hook and loop / White elastic band		EN ISO 11611:2015, point 6.7.2 The flame does not reach the upper or either vertical edge No flaming or molten debris - Afterglow ≤ 2s - Afterflame ≤ 2s Closure system open at least once	± 8,8 %	AR-22-YL-004012-01	M
Small splashes of molten metal, after pre-treatment point 6.8	Grey fabric	ISO 9150	EN ISO 11611:2015, point 6.8 Class 1: ≥ 15 and < 25 drops Class 2: ≥ 25 drops	± 3 drops	AR-22-YL-007259-01	Class 2 M
Heat transfer (radiation), after pre-treatment point 6.9	Grey fabric	ISO 6942 (Method B)	EN ISO 11611:2015, point 6.9 Class 1: 16 > RHTI 24 ≥ 7 Class 2: RHTI 24 ≥ 16	± 0,6 %	AR-23-YL-100632-01	Class 2 M
Electrical resistance, after pre-treatment point 6.10	Grey fabric	EN 1149-2	EN ISO 11611:2015, point 6.10 > 10 ⁵ Ω	± 15 %	AR-22-YL-004012-01	M
Fat content of leather point 6.11	Leather	ISO 4048:2008	EN ISO 11611:2015, point 6.11 ≤ 15%	NA	NA	NA
Marking point 7	EN ISO 11611:2015, point 7 + EN ISO 13688, point 7			NA	NA	M
Information supplied by the manufacturer point 8	EN ISO 11611:2015, point 8 + EN ISO 13688, point 8			NA	NA	M

- **EN 1149-5:2018** Protective clothing – Electrostatic properties – Part 5: Material performance and design requirements

TEST	APPLIES ON	STANDARD	REQUERIMENTS	*UoM.	REPORT N°	RESULT
Material requirements point 4.2.1	Electrostatic dissipative material	EN 1149-5:2018, point 4.2.1	EN 1149-5:2018, point 4.2.1	NA	NA	M
Half decay time (either geometric mean) ⁽¹⁾ point 4.2.1	Grey fabric	EN 1149-3:2004 (Method 2)	EN 1149-5:2018, point 4.2.1 $t_{50} < 4s.$	$\pm 17 \%$	AR-22-YL-004012-01	M
Shielding factor (arithmetic mean) ⁽²⁾ point 4.2.1	External material		EN 1149-5:2018, point 4.2.1 $S > 0,2$	NT	NT	NT
Surface resistance (geometric mean) ⁽³⁾ point 4.2.1	External material	EN 1149-1	EN 1149-5:2018, point 4.2.1 $\leq 2,5 \cdot 10^9 \Omega$	NT	NT	NT
Design requirements point 4.2.2	Garment	EN 1149-5:2018, point 4.2.2	EN 1149-5:2018, point 4.2.2	NA	Point 5 of this report	M
Conductive parts (if applicable) point 4.2.2.3	Metal/conductive elements outside (slide fasteners, buttons, ...)	EN 60079-32-2:2015	EN 1149-5:2018, point 4.2.2.3 $< 3pF$	NA	NA	NA
Marking point 5	EN 1149-5:2018, point 5			NA	NA	M
Information supplied by the manufacturer point 6	EN 1149-5:2018, point 6			NA	NA	M

^{(1), (2) o (3)} *Not necessarily all three requirements*

9. CONCLUSION

Based on the results obtained in the exams, evaluations and revisions the following can be deduced:

The PPE type **SLEEVES** reference **38-4321**, classified as Category **II** Individual Protective Equipment and whose characteristics are stated in point 1 of this report, **COMPLIES** with the essential requirements established by Regulation (EU) 2016/425 of 9 March 2016 through the application of the standards and risks as stated in point 2 of this report.

On 23rd of December 2022

Signature of the conformity evaluator: